

PAT-NO: JP02001060804A

DOCUMENT-IDENTIFIER: JP 2001060804 A

TITLE: DIELECTRIC RESONATOR AND DIELECTRIC  
FILTER

PUBN-DATE: March 6, 2001

INVENTOR-INFORMATION:

NAME	COUNTRY
KO, SAIKO	N/A
FURUTA, ATSUSHI	N/A
ISOMURA, AKIHIRO	N/A

ASSIGNEE-INFORMATION:

NAME	COUNTRY
TOKIN CORP	N/A

APPL-NO: JP11233683

APPL-DATE: August 20, 1999

INT-CL (IPC): H01P001/208, H01P001/20 , H01P001/205 ,  
H01P007/10

ABSTRACT:

PROBLEM TO BE SOLVED: To provide a triple-mode dielectric resonator with a very small and simple configuration and a dielectric filter using such a dielectric resonator.

SOLUTION: This dielectric resonator 10, which has three faces formed by scraping away three edges parts sharing one point of a dielectric block and other three faces respectively adjoining one another and

forming a face 2b by scraping away another edge that is not parallel with the edge is arranged in a cutoff waveguide 3, and a dielectric filter is constructed by providing bar-shaped antennas 8 whose one end is in open state and input-output terminals 9 as an energizing means. Miniaturization and cost reduction can be achieved since characteristics corresponding to a three-stage filter can be obtained by using only one dielectric block 1.

COPYRIGHT: (C) 2001, JPO

PAT-NO: JP02001060805A

DOCUMENT-IDENTIFIER: JP 2001060805 A

TITLE: DIELECTRIC RESONATOR AND DIELECTRIC  
FILTER

PUBN-DATE: March 6, 2001

INVENTOR-INFORMATION:

NAME	COUNTRY
FURUTA, ATSUSHI	N/A
KO, SAIKO	N/A
ISOMURA, AKIHIRO	N/A

ASSIGNEE-INFORMATION:

NAME	COUNTRY
TOKIN CORP	N/A

APPL-NO: JP11233684

APPL-DATE: August 20, 1999

INT-CL (IPC): H01P001/208, H01P001/20 , H01P007/10

ABSTRACT:

PROBLEM TO BE SOLVED: To materialize a dielectric resonator which reduces the number of dielectric resonators, is miniaturized, realizes cost reduction and is also excellent in an extraband characteristics.

SOLUTION: One triple mode dielectric resonator combining three resonation modes of a dielectric block 1 by forming a face 2a by scraping away one edge of block 1 having a substantially rectangular parallelepiped shape and also

where an angle made  
between a scraped face and its adjoining face ranges  
between 40 and 50 degrees  
and the area ratio of the scraped face to the adjoining  
face ranges between 1  
and 200%, is installed in a hollow shield case 21 being of  
an almost  
rectangular parallelepiped shape, and is provided with  
supplying and receiving  
electric probes 24 and 25 to construct a dielectric filter.

COPYRIGHT: (C)2001,JPO

[IEEE HOME](#) | [SEARCH IEEE](#) | [SHOP](#) | [WEB ACCOUNT](#) | [CONTACT IEEE](#)[Membership](#) [Publications/Services](#) [Standards](#) [Conferences](#) [Careers/Jobs](#)**IEEE Xplore**  
RELEASE 1.4Welcome  
United States Patent and Trademark Office[Help](#) [FAQ](#) [Terms](#) [IEEE Peer Review](#) [Quick Links](#)

Welcome to IEEE Xplore

[SEARCH RESULTS](#)[\[PDF Full-Text \(313 KB\)\]](#)[NEXT](#)[DOWNLOAD CITATION](#)

- ☐ Home
- ☐ What Can I Access?
- ☐ Log-out

**Tables of Contents**


- ☐ Journals & Magazines
- ☐ Conference Proceedings
- ☐ Standards

**Search**

- ☐ By Author
- ☐ Basic
- ☐ Advanced

**Member Services**

- ☐ Join IEEE
- ☐ Establish IEEE Web Account
- ☐ Access the IEEE Member Digital Library

 [Print Format](#)

## A practical triple-mode monoblock bandpass filter base station applications

Chi Wang Wilber, W. Engst, B.

Radio Frequency Syst. Inc., Marlboro, NJ;

*This paper appears in: **Microwave Symposium Digest, 2001 IEEE MTT-S International***

05/20/2001 -05/25/2001, 2001

Location: Phoenix, AZ, USA

On page(s): 1783-1786 vol.3

Volume: 3, 2001

References Cited: 9

Number of Pages: 3 vol.(lxiii+xxiv+xxiii+2262)

INSPEC Accession Number: 7024059

**Abstract:**

A practical triple-mode dielectric monoblock band pass filter integrated with a bandwidth pre-select mask bandpass filter and a microstrip low pass filter for WCDMA base station application is presented. The dielectric monoblock triple-mode filter was designed and optimized using 3D EM simulation software incorporating the equivalent circuit model. The pre-select filter and low pass were used to clean up the spurious response of the triple-mode filter up to 12 GHz. Both triple mode and mask filters are directly mounted on the PCB to minimize cost and loss.

**Index Terms:**

band-pass filters code division multiple access dielectric losses equivalent circuits microwave filters passive filters waveguide filters 0 to 12 GHz 3D EM simulation software WCDMA base station applications cost dielectric filters equivalent circuit model low pass filter microstrip low pass filter pre-select mask bandpass filter spurious response triple-mode monoblock bandpass filter

**Documents that cite this document**

Select link to view other documents in the database that cite this one.

[SEARCH RESULTS](#)[\[PDF Full-Text \(313 KB\)\]](#)[NEXT](#)[DOWNLOAD CITATION](#)

[Home](#) | [Log-out](#) | [Journals](#) | [Conference Proceedings](#) | [Standards](#) | [Search by Author](#) | [Basic Search](#) | [Advanced Search](#) | [Join IEEE](#) | [Web Account](#) | [New this week](#) | [OPAC Linking Information](#) | [Your Feedback](#) | [Technical Support](#) | [Error Report](#) | [No Robots Please](#) | [Release Notes](#) | [IEEE Online Publications](#) | [Help](#) | [FAQ](#) | [Terms](#) | [Back to Top](#)